

DEVELOP

Dynamic balance

www.develop.eu

ineo 950

monochrome | up to 5,700 pph



ineo 950

GENERAL DATA

Type of machine

Console system (built-in scanner)

Printing and copying speed

- > A4, max. 95 ppm, max. 5,700 pph
- > A3, max. 55 ppm, max. 3,300 pph

Print system

Laser

Gradation

256

Paper feeder

- > Standard: 2,150 sheets, max. 6,650 sheets
- > 2 x 500 sheets per cassette (40 – 216 g/m²)
- > 1 x 1,000 sheets per cassette (40 – 216 g/m²)
- > 1 x 150 sheets multi bypass (40 – 244 g/m²)

Paper format

Max. 314 x 460 mm

Printable area

Approx. 303 x 456 mm

Warm-up time

Less than 330 seconds

Dimensions (w x d x h)

980 x 1,428 x 869 mm (without options)

Weight

Approx. 285 kg (only main body)

Power

230 V / 50 Hz

PRINT SPECIFICATIONS

Controller

- > Embedded PCL controller, 2 GHz
- > Optional: PostScript 3

Memory

2 GB RAM, 160 GB HDD

Resolution

Print: max. 2,400 x 600 dpi
(with Smoothing Technology)

Network protocols

TCP/IP, IPX/SPX, NetBEUI, Ethertalk, IPP

Emulation

PCL 5e/XL (PCL 6)

Interfaces

Ethernet 10/100/1000 BaseT, USB 2.0

Driver

Windows 2000/2003/XP/Vista
Mac OS 10.2, 10.4, 10.5

Print functions

Electronic sorting, duplex, N-up print, Tab print, watermark, Mixmedia and Mixplex

SCAN SPECIFICATIONS

Type of scanning

TWAIN-Scan, Scan to E-mail/FTP/HDD/SMB (PC)

Resolution

Max. 600 x 600 dpi

Scanning speed

Max. 95 opm

Size of originals

Max. A3

Scanning formats

PDF, TIFF

Scan addresses

LDAP-support

COPY SPECIFICATIONS

Document feeder

- > Max. A3
- > Duplex document feeder
(100 sheets, max. 200 g/m²)

Copy pre-selection

1 – 9,999

Zoom

25 – 400 % in 0.1 % steps

First A4 copy

less than 3.1 seconds

Memory

256 MB RAM

HDD

160 GB

Resolution

Max. 600 x 600 dpi

Copier functions

Chapter and cover mode, proof copy, 8/4/
2-to-1 copy, duplex, book copy, image overlay,
watermark

OPTIONS

- > Booklet finisher
(2,700-sheet collection)
- > Finisher with 100-sheet multi-position
stapling (3,200-sheet collection)
- > Optional for all finishers:
Punch Kit (A5 – A3, 50 – 128 g/m²),
Post Insertion Unit for cover sheets
(A5 – A3, 50 – 200 g/m²), Z-fold & Punch Unit
- > Trimming Unit (A4/A3, max. 100-sets collection)
- > Large-capacity cassette, A4 4,500 sheets
(A4, 40 – 300 g/m²)
- > Large-capacity cassette, A3+ 4,000 sheets
(A4/A3+, 40 – 300 g/m²)
- > PostScript 3

WORKFLOW UTILITIES

- > dots Pilot 2 imposition (optional)
- > Print pool manager load balancing (optional)
- > Jtman 4 jobticket (optional)
- > Jtweb 4 jobsubmission (optional)
- > ineo Remote Care (optional)
- > Enterprise Device Manager (optional)

DEVELOP

Develop GmbH Hessenstraße 1 30855 Langenhagen Germany www.develop.eu



COPYLANDIA
The Total Document Solutions Provider
Juan Luna Ave. cor. De Veyra St.
North Reclamation Area, Mabolo, Cebu City
CALL 232-4520 www.copylandia.com

All data relating to the paper capacities of the document feeder, the final processing accessories and the paper cassettes apply to paper weighing 80 g/m² unless expressly stated otherwise.

All data relating to the speed of printing, scanning or faxing apply to paper of an A4 format weighing 80 g/m² unless expressly stated otherwise.

All data relating to paper weights apply to media that are recommended by DEVELOP

All technical data correspond to knowledge available at the time of going to print. DEVELOP reserves the right to make technical alterations. DEVELOP and ineo are registered trademarks/product titles owned by DEVELOP GmbH. All other brand or product names are registered trademarks or product titles of their respective manufacturers. DEVELOP does not accept any liability or guarantee for these products.

Printed in Germany on chlorine-free bleached paper.

4854901099500 | April 2009